



Model

12CFB

Carry-All Scraper
for Ag tractors in the 180 hp. to 230 hp. range



FEATURES

- Ruggedly built . . . material electrically welded for maximum strength and rigidity.
- Fixed blade feature is designed specifically for achieving a smooth, precision laser finish.
- Direct loading lets the loading pressure push the soil into the bucket.
- Units can be used in single or tandem configurations and are laser adaptable.
- One piece, reversible (double edge), heat treated alloy steel blade ensures durability and a long service life.
- Separate gate and bucket hydraulic control gives more yardage on every cycle.
- Heavy-duty, yoke- type, multi-positional hitch.
- Four 17.5 x 25 - 16 PR radial loader / dozer tires. (CS)
- Quick hitch of hydraulic lines at rear of tractor to facilitate maximum utilization of tractor in other work.



Specifications

Series 12CFB12 Fixed Blade Carry-All Scraper

Rome Carry-All Scrapers (Pull Type)		Model 12CFB12
Capacity Heaped (SAE): Cubic yards (cubic meters) (1:1 Slope)		12 (9.2)
Capacity Struck (SAE): Cubic yards (cubic meters)		8.6 (6.6)
Overall Dimensions:	Length / inches (centimeters)	245" (622)
	Width / inches (centimeters)	163 (414)
	Height / inches (centimeters)	78" (198)
Bucket Dimensions:	Length / inches (centimeters)	68" (173)
	Width / inches (centimeters)	144" (366)
	Height / inches (centimeters)	41" (104)
Transport Clearance: inches (centimeters)		14" (36)
Weight: pounds (kilograms)		13,000 (5897)
Payload Wt. @ 2250 lbs. / cu. yds.: pounds (kilograms)		27,000 (12247)
Weight Distribution:	Tongue	31%
	Wheels	69%
Tires - Number, size and type:		(4) 17.5 x 25 -16 PR radial loader / dozer (CS)
Width of Cut: feet / inches (centimeters)		12' / 144" (366)
Horsepower Required:		180-230
Blade Type:	One piece, Alloy (high carbon) steel, double edge (reversible), Overall Width -163"	
Hydraulic Cylinders:	Frame (Carriage)	Two each 6" x 12"
	Bucket	Two each 3 -1/2" x 27"
	Gate	One each 6" x 13-1/8"
Hydraulics Required:		Two Double Acting Circuits, 25 gpm @ 2500 psi.
Type of Loading:		Direct
Type of Dumping:		Gravity via Bucket Pivot
Drawbar Type:		Rome Special Tractor Drawbar
Hitch Type - with standard bolt-on tongue assembly		Heavy Duty Yoke, Multi-positional
Tandem Hitch:		Rear Hitching Capability
Laser Adaptable - optional attachment bracket available		Yes



ROME PLOW EQUIPMENT CO., LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.