



**Model**

**C17E10.5**

**High Performance Ejector Scraper**  
for Agricultural tractors from 300 hp. to 400 hp.



A 17 cubic yard Ejector Scraper that is ideally suited for both agricultural and construction jobs. Economically build roads, construct and maintain terraces, levees and ponds, airports, general construction and mining applications. Laser adaptable to allow the contractor to finish grade to exact specifications and the farmer to precision level fields.

## **FEATURES**

- Ruggedly built . . . material electrically welded for maximum strength and rigidity.
- Multi-Function hydraulic valve block. ■ Ejector / floor roller bearings.
- Tandem hitch and hydraulics. ■ Cylinder safety stops. ■ Laser receiver bracket.
- Reversible, three piece, heat treated alloy steel blade. Serrated / plain center stinger section. ■ Heavy-duty, yoke- type, multi-positional hitch. ■ Flare type fittings reduce leaks. ■ Covers protect lines. ■ Wear resistant cast bits. ■ Height adjustable axle mounts. ■ Heavy-duty roller bearing hubs. ■ Four 20.5 R25 VUT Radial Tires (CS).



## Specifications

Model	Capacity		Width of Cut	Transport Dimensions				Approx. Weight
	Struck	Heaped		Width	Length	Height	Clearance	
C17E10.5	14.0 yd <sup>3</sup> (10.6 m <sup>3</sup> )	17.0 yd <sup>3</sup> (13.0 m <sup>3</sup> )	126 in. (4.27 m)	144" (3.65 m)	266" (6.75 m)	81" (2.05 m)	20" (0.50 m)	23, 600 lbs. (10705 kg)

### Additional Features and Benefits:

■ **Tractor Hydraulic Requirements -**

Two double acting circuits - optimum 25 GPM (100 l / min) at 2500 PSI (175 bar). Two hoses per circuit - tractor to scraper.

■ **Scraper Hydraulic Requirements -**

Two each 4 x 39.50 ejector cylinders. One 6 x 16 gate cylinder. Two each 6 x 19.25 carriage cylinders.

■ **Hydraulic System-**

With manifold. Integral valves to control all scraper functions. Flare type fittings to reduce leaks. Covers protect lines. Easy service access.

■ **Synchronized Ejector -**

Cylinders, priority apron opening system, replaceable flat ejector guide rails and steel rollers.

■ **Engine Horsepower Requirements -**

One Scraper        300 - 350 HP  
Two Scrapers      350 - 400 HP

■ **Options -**

Straight blade in lieu of serrated / smooth extended center blade for flat finish.



### ROME PLOW EQUIPMENT CO.,LLC

475 Sixth Street  
P.O. Box 48,  
Cedartown, GA 30125, USA  
[www.romeplow.com](http://www.romeplow.com)

Telephone: (770) 748-4450  
(800) 241-7860 (USA)  
Fax: (800) 553-2865 (USA)  
Fax: 770-748-4427

Materials and specifications subject to change without notice. Printed in U.S.A.

This document was created with Win2PDF available at <http://www.daneprairie.com>.  
The unregistered version of Win2PDF is for evaluation or non-commercial use only.