



Models
12C10LGP
14CS10LGP
16C10LGP
17C12LGP
17CS12LGP

Low Ground Pressure Carry-All Scrapers **for Agricultural tractors from 150 hp. to 400 hp.**

high floatation special application scrapers



move sand and muck soil with agricultural tractors . . .

FEATURES

- Ruggedly built . . . material electrically welded for maximum strength and rigidity.
- Efficient, self-loading bucket design productively excavate, transport and spread material with minimum rolling resistance and power requirements. ■ The two 43" wide super floatation tires eliminate mud build-up between side walls. Reduced tire rutting improves ground speed of the equipment and makes for a more economical operation.
- Tandem hitch and hydraulics. ■ Laser receiver bracket. ■ Heavy-duty, yoke-type, multi-positional hitch. ■ Flare type fittings reduce leaks. ■ Covers protect lines. ■ Wear resistant cast bits. ■ Height adjustable axle mounts. ■ Reversible, three piece, heat treated alloy steel blade with removable center stinger section.
- Heavy-duty roller bearing hubs. ■ The reliable hydraulic controls have fail-safe gate opening sequence valve. Tandem hitch lowers rear scraper when front unit is raised.



Specifications

Model	Capacity		Width of Cut	Transport Width	Tires 20 PR	Rims	Approx. Weight
	Heaped	Struck					
12C10LGP	12.0 yd ³ (9.17 m ³)	8.6 yd ³ (6.57 m ³)	120" (3.05 m)	137" (3.48 m)	66 x 43 - 25	36 x 25	14,000 lbs (6350 kg)
14CS10LGP	14.0 yd ³ (10.70 m ³)	10.7 yd ³ (8.18 m ³)	120" (3.05 m)	137" (3.48 m)	66 x 43 - 25	36 x 25	14,800 lbs (6713 kg)
16C10LGP	16.0 yd ³ (12.23 m ³)	12.0 yd ³ (9.17 m ³)	120" (3.05 m)	137" (3.48 m)	66 x 43 - 25	36 x 25	18,000 lbs (8165 kg)
17C12LGP	17.0 yd ³ (12.99 m ³)	13.0 yd ³ (9.93 m ³)	144" (3.66 m)	163" (14.14 m)	66 x 43 - 25	36 x 25	18,000 lbs (8165 kg)
17CS12LGP	17.0 yd ³ (12.99 m ³)	13.0 yd ³ (9.93 m ³)	144" (3.66 m)	163" (14.14 m)	66 x 43 - 25	36 x 25	18,500 lbs (8391 kg)

■ Tractor Hydraulic Requirements -

Two double acting circuits - optimum 25 GPM (95 l / min) at 2500 PSI (175 bar). Two hoses per circuit - tractor to scraper.

■ Engine Horsepower Requirements -

Scraper Model	Single Scraper	Tandem Scraper
12C10LGP	150-200	200-250
14CS10LGP	200-250	250-300
16C10LGP	250-300	300-350
17C12LGP and 17CS12LGP	300-350	350-400

■ Options -

Even center blade in lieu of standard extended center blade for flat finish.



ROME PLOW EQUIPMENT CO.,LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.