

ROME

Series

RV

Vee Blade Cutters

for use with Caterpillar D7, D8 and D9 tractors



FEATURES

- Ruggedly built with all-welded construction . . . for maximum strength, rigidity and durability to assure long life with a minimum of maintenance.
- Excellent balance and floatation for better footing on soft ground.
- Serrated blades of tough T-1 steel shear small trees and vegetation off at ground level and windrow to one side . . . all in one pass.
- Center-mounted knife-sharp “stinger” splits and weakens large trees by concentrating full weight and horsepower of the tractor into powerful splitting and shearing force.
- Cutting patterns can be in any direction to meet wind and terrain conditions which might otherwise limit movement of the tractor.
- Rapid, economical removal of all vegetation at ground level with a minimum of soil disturbance.



Specifications Series RV-Vee Blade Cutters

Model Number	Overall Length Trunnion to Stinger Tip	Overall Width Mounted	Height	Net Wt. lbs.
For Caterpillar D7F Tractors, serial nos. 93N and 94N and for Caterpillar D7G Tractors, serial nos. 91V1-up and 92V-up.				
RV7	20' - 2"	12' - 0"	4' - 1"	9,550
For Caterpillar D7H and D7R Tractors with standard track.				
RV7H	20' - 2"	12' - 0"	4' - 1"	9,655
For Caterpillar D8H Tractors, serial nos. 36A and 46A.				
RV8H	24' - 0"	14' - 0"	4' - 5"	12,970
For Caterpillar D8K Tractors, serial nos. 76V1-up and 77V1-up.				
RV8K	24' - 0"	14' - 0"	4' - 5"	12,970
RV8L	24' - 8"	14' - 0"	4' - 4"	13,385
For Caterpillar D8N Tractor.				
RV8N	24' - 0"	14' - 0"	4' - 4"	13,385
For Caterpillar D8R Tractor.				
RV8R	24' - 0"	14' - 0"	4' - 4"	13,385
For Caterpillar D9N Tractor.				
RV9N	24' - 1"	14' - 2"	4' - 4"	14,385

Notes: Series RV Vee Blade Cutters are furnished as a complete unit for mounting on the trunnions of a Caterpillar track-type tractor. No trunnions, hydraulic cylinders or components furnished by Rome. Maximum usable track width same as recommended by Caterpillar Inc. for C-Frames.

When ordering Series RV Vee Blade Cutters for Caterpillar track-type tractors, specify tractor serial number.

Shipping width of the D8 size Vee Blade Cutter is 12'. Two one-foot cutting edge extensions are furnished with each cutter assembly. These are to be field welded by the dealer, using E11018G welding rods, which are furnished by Rome. The effective cutting width with extensions is 14'.

An over width permit is required for shipping all RV Series Vee Blade Cutters.

When utilizing "V" Blade on D8L, it is recommended that rear counterweight 3T8710 (4692 lbs.) be used.



ROME PLOW EQUIPMENT CO.,LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.