



Series

TAW

Wheel Offset Disk Harrows

For use with tractors in the 73 to 168 horsepower range



FEATURES

- | Heavy - duty proven design - rugged, boxed angle construction, welded for maximum strength and rigidity.
- | Dual purpose transport unit for transportability and penetration control.
- | Combines ease of maneuverability with high strength for the most adverse conditions.
- | Adjustable disk blade scrapers. | Tapered roller gang bearings - greaseable
- | High gang carrier design to prevent trash build-up and clogging.
- | Up to 384 pounds of weight per disk blade, depending on model.
- | Full range of adjustments to control depth of penetration - up to 9 inches maximum with standard 28 inch disk blade.
- | Levels, cuts and mixes to full working depth.



Specifications

Series TAW Wheel Offset Disk Harrows

12" (304.8 mm) Disk Spacing; 2-1/8" (54 mm) Round Axles. Equipped With Dual Tapered Roller Bearings.

Model Number	Width of Cut	No. of Disks	* Suggested		Wt. per Disk lbs.	Net Weight lbs.
			DB. PP.	DB. HP.		
TAW-16	7' - 6"	16	7800 - 9800	73 - 91	379	6,067
TAW-20S	9' - 6"	20	9100 - 11100	85 - 104	352	7,044
TAW-24	11' - 6"	24	10900 - 12900	102 - 120	346	8,313
TAW-28	13' - 6"	28	14500 - 16500	135 - 154	384	10,748
TAW-32	15' - 6"	32	16000 - 18000	149 - 168	369	11,811

* Drawbar Pounds Pull, PTO Horsepower and Drawbar Horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Harrow weights shown are with standard 28" x 3/8" thick, cutout, deep concavity disk blades.

Standard Equipment

- ‡ 28" (711 mm) dia., 3/8" (10 mm) thick, cutout (notched) deep concave. disk blades.
- ‡ New Low Profile Tires.
TAW-16 thru TAW-24
12.5L x 15 -12 ply - F1 Highway Service (2)
TAW-28, TAW-32
21.5L x 16.1 -12 ply (2)
- ‡ Adjustable disk blade scrapers.
- ‡ Hydraulic Control Group:
Includes hydraulic cylinder, (hoses with fittings to reach rear of tractor and hose holder).
- ‡ Heavy Duty Bearing Wear Plates.

Per ASAE S290.1. Width of Cut will vary with gang angle and blade diameter

Optional Equipment

- ‡ Disk Blades
30" x 3/8". Cutout (notched), deep concavity.
- ‡ Disk Blades
30" x 1/2". Cutout (notched), deep concavity.
- ‡ Cylinder Rod Stops - all models.

Note: TAW-20S is a Special Model.

The front gang assembly is strengthened with two additional gang bearings.

All models require hydraulic control.

*Drawbar pounds pull and drawbar horsepower will vary according to soil conditions and weight added to harrow.



ROME PLOW EQUIPMENT CO., LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.