

ROME

Series

TRH-S

Heavy-Duty Hinge Offset Harrows

for tractors in the 110 to 225 DBHP range



FEATURES

- | For plowing and plowing after clearing.
- | Reinforced for woods site preparation and other severe applications.
- | Heavy -duty proven design -rugged, boxed angle construction, welded for maximum strength and rigidity.
- | High gang carrier design to prevent trash build-up and clogging.
- | Tapered roller gang bearings - greaseable | Adjustable disk blade scrapers.
- | Up to 645 pounds of weight per disk blade, depending on model.
- | Full range of adjustments to control depth of penetration - up to 10 inches maximum penetration with standard 32 inch disk blade.
- | Levels, cuts and mixes to full working depth.



Specifications

TRH-S Hinge Offset Disk Harrows

14" (356 mm) Disk Spacing; 2-1/2" (63.5 mm) Round Axles. Equipped With Dual Tapered Roller Bearings.

Model Number	Width of Cut	No. of Disks	*Suggested		Wt. Per Disk lbs.	Net Wt. lbs.
			DB.PP.	DB.HP.		
TRH-14S	7' - 6"	10	11700-13700	109-128	645	9,024
TRH-16S	9' - 0"	16	13400-15400	125-144	647	10,344
TRH-20S	11' - 0"	20	14800-16800	138-157	569	11,370
TRH-24S	13' - 6"	24	18500-20500	173-191	582	13,975
TRH-28S	15' - 6"	28	22100-24100	206-225	595	16,657

*Drawbar Pounds Pull, PTO Horsepower and Drawbar Horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Harrow weights shown are with standard 36" x 1/2" thick, cutout, deep concavity disk blades.

Standard Equipment

- ! 32" (813 mm) dia., 1/2" (12 mm) thick, cutout (notched) deep concavity disk blades.
- ! Special Reinforcement for woods application - includes strengthened gang carriers, drawbar, offset bar, stabilizer, latch, bearing standards and heavier duty bearing brackets.
- ! Mechanical angling control.
- ! Hydraulic Control Group: Includes hydraulic cylinder, (hoses with fittings to reach rear of tractor and hose holder).
- ! Bearing Wear Plates. ! Scrapers

Per ASAE S290.1. Width of Cut will vary with gang angle and blade diameter

Optional Equipment

- ! Cylinder Rod Stops - all models.
- ! Weight Box - all models
 - TRH-14S wt. 470 lbs
 - TRH-16S thru TRH-24S wt. 600 lbs.

* Drawbar pounds pull and drawbar horsepower will vary according to soil conditions and weight added to harrow



ROME PLOW EQUIPMENT CO., LLC

475 Sixth Street Telephone: (770) 748-4450
 P.O. Box 48, (800) 241-7860 (USA)
 Cedartown, GA 30125, USA Fax: (800) 553-2865 (USA)
www.romeplow.com Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.