

ROME

Series

TRW

Heavy-Duty Wheel Offset Harrows

For use with tractors in the 174 to 216 horsepower range

TRW-S

Heavy-Duty (woods special) Harrows

For use with tractors in the 162 to 194 horsepower range



FEATURES

- ! For plowing after clearing. Series TRW-S reinforced for severe woods site preparation.
- ! High gang carrier design to prevent trash build-up and clogging.
- ! Rugged boxed angle construction, welded for maximum strength and rigidity.
- ! Tapered roller gang bearings - greaseable. ! Adjustable disk blade scrapers.
- ! Full range of adjustments to control penetration depth under varying conditions.
- ! Up to 810 pounds (367 kilograms) of weight per disk blade, depending on model.
- ! Up to 10" (254 mm) maximum depth of penetration with standard 32" disk blade.
- ! Dual purpose transport unit serves for transportability and penetration control.



Specifications

Series TRW Heavy-Duty Wheel Offset Disk Harrows

Series TRW-S Heavy-Duty Wheel Offset Disk Harrows - Woods Special

14" (356 mm) Disk Spacing; 2-1/2" (63.5 mm) Round Axles. Equipped With Dual Tapered Roller Bearings.

Model Number	Width Of Cut ft. / in.	No. of Disks	*Suggested		Wt. per Disk lbs.	Net Wt. lbs
			DB. PP.	DB. HP.		
TRW - 20	11" - 0"	20	18600 -20600	174 -192	692	13,833
TRW - 24	13" - 6"	24	21100 -23100	197 - 216	653	15,672
TRW-16S	9' - 0"	16	17400 -19400	162 - 181	810	12,963
TRW-20S	11' - 0"	20	18800 -20800	175 - 194	703	14,068

* Drawbar Pounds Pull, PTO Horsepower and Drawbar Horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Harrow weights shown are with standard 32" x 1/2" thick, cutout, deep concavity disk blades.

Standard Equipment

- | 32" (813 mm) dia., 1/2" (12 mm) thick, cutout (notched) deep concavity disk blades.
- | New Industrial Tires.
15 x 22.5 - 16 ply rating.
- | Adjustable Disk Blade Scrapers.
- | Bearing Wear Plates.
- | Greaseable Bearings.
- | Hydraulic Control Group:
Includes hydraulic cylinder, (hoses with fittings to reach rear of tractor and hose holder).

Per ASAE S290.1. Width of Cut will vary with gang angle and blade diameter.

Standard Equipment continued

- | Special reinforcement for woods application includes strengthened frame, drawbar, offset bar, bearing standards and heavier duty bearing brackets.
- Models TRW-16S and TRW-20S only.**

Optional Equipment

- | Cylinder Rod Stops - all models

*Drawbar pounds pull and drawbar horsepower will vary according to soil conditions and weight added to harrow.



ROME PLOW EQUIPMENT CO.,LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.win2pdf.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.
This page will not be added after purchasing Win2PDF.