



Series
TCW

Wheel Offset Disk Harrows

for use with tractors in the 37 to 168 horsepower range



FEATURES

- | High gang carrier design to prevent trash build-up and clogging.
- | Boxed angle construction, welded for maximum strength and rigidity.
- | Tapered roller gang bearings - greaseable.
- | Adjustable disk blade scrapers.
- | Up to 178 pounds (80 kilograms) average of weight per disk blade, depending on model.
- | Up to 8 (204 mm) inches maximum depth of penetration with standard 24 inch disk blade.
- | Dual purpose transport unit serves for transportability and penetration control.



Specifications

Series TCW Wheel Offset Disk Harrows

9" (229 mm) Disk Spacing; 1-5/8" (41.3 mm) Round Axles. Equipped With Dual Tapered Roller Bearings.

| Model Number | Width Of Cut | No. of Disks | * Suggested | | Wt. per Disk lbs. | Net Weight lbs. |
|--------------|--------------|--------------|-------------|---------|-------------------|-----------------|
| | | | DB. PP. | DB. HP. | | |
| TCW-16 | 6' - 0" | 16 | 2500-4500 | 23-42 | 175 | 2,813 |
| TCW-18 | 7' - 0" | 18 | 2600-4600 | 24-43 | 171 | 3,082 |
| TCW-20 | 7' - 6" | 20 | 3100-5100 | 29-49 | 177 | 3,557 |
| TCW-24 | 9' - 0" | 24 | 3900-5900 | 36-55 | 165 | 3,982 |
| TCW-28 | 10' - 6" | 28 | 5100-7100 | 41-66 | 178 | 4,984 |
| TCW-32 | 12' - 0" | 32 | 5900-7900 | 55-74 | 174 | 5,576 |
| TCW-36 | 14' - 0" | 36 | 6200-8200 | 58-77 | 164 | 5,923 |
| TCW-40 | 15' - 6" | 40 | 7200-9200 | 67-86 | 166 | 6,660 |

* Drawbar Pounds Pull, PTO Horsepower and Drawbar Horsepower are suggested ranges and vary according to soil conditions and weight added to harrow. Harrow weights shown are with standard 24" x 1/4" thick, cutout, deep concavity disk blades.

Standard Equipment

- ‡ 24" (609 mm) dia., 1/4" (6.4 mm) thick, cutout (notched) deep concavity disk blades.
- ‡ New Industrial Tires.
TCW-16 thru TCW-24, 12.5Lx 15 – 12 ply
TCW-28, TCW-32, 7.5 x 16 – 12 ply
TCW-36, TCW-40, 12.5L x 15 – 12 ply
- ‡ Scrapers ‡ Tongue Jack and Safety Chain.
- ‡ Hydraulic Control Group:
Includes hydraulic cylinder, (hoses with fittings to reach rear of tractor and hose holder).
- ‡ Heavy Duty Bearing Wear Plates.

Per ASAE S290.1. Width of Cut will vary with gang angle and blade diameter.

Optional Equipment

- ‡ Disk Blades
26" x 1/4". Cutout (notched), deep concavity.
- ‡ Cylinder Rod Stops - all models.
TBW-16 thru TBW-24 wt. 6 lbs.
TBW-32 wt. 11 lbs.
TBW-40 wt. 11 lbs.

* Drawbar pounds pull and drawbar horsepower will vary according to soil conditions and weight added to harrow



ROME PLOW EQUIPMENT CO., LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.