

ROME

Series

RSR

Inline Subsoiler Ripper

for Three Point Hitch-Category III, 4-N Arrangement



FEATURES

- ‡ Computer aided design increases efficiency and performance.
- ‡ Mainframe constructed of tough, high-strength 7" x 7" x 3/8" welded rectangular tubing.
- ‡ Bolt-on shanks and coulters permit quick changes in spacing when desirable.
- ‡ Fits the Three Point Hitch - Category III, 4-N to make transportation between jobs easier.
- ‡ Deep soil mulching action reduces water erosion and helps the farmer field produce the highest yield possible while complying with today's strict conservation and erosion regulations.
- ‡ Keeps moist soil beneath the surface and away from the sun and wind.
- ‡ Provides a deep, clean "slice" that breaks up hardpan to increase water intake, reduce water run off and enhance root structure environment for superior crop growth.
- ‡ Shear bolt protection.
- ‡ Gauge wheels assure accurate penetration control in shallow or deep applications.



Specifications

Series RSR - Inline Subsoiler Ripper

| Model Number | Width of Frame ft. in. | Number of Shanks | Number of Coulters | Shank / Coulters Spacing inches | Gauge Wheels six - bolt hub | Wt. w / o Coulters lbs. | Wt. with Coulters lbs. |
|--------------|---------------------------|------------------|--------------------|------------------------------------|--------------------------------|----------------------------|---------------------------|
| RSR11-3 | 11' - 0" | 3 | 3 | 36" - 40" - 60" | Two, single | 1,953 | 2,175 |
| RSR11-5 | 11' - 0" | 5 | 5 | 30" | Two, single | 2,305 | 2,675 |
| RSR16-5 | 16' - 0" | 5 | 5 | 36" - 40" | Two, single | 2,740 | 3,110 |
| RSR16-7 | 16' - 0" | 7 | 7 | 30" | Two, single | 3,092 | 3,610 |
| RSR21-7 | 21' - 0" | 7 | 7 | 36" - 40" | Two, single | 3,527 | 4,045 |
| RSR21-9 | 21' - 0" | 9 | 9 | 30" | Two, single | 4,314 | 4,980 |

Standard Equipment

- | Operator's Manual container.
- | Stout 7" x 7" x 3/8" square tube framework.
- | 1-1/4" x 8" - high strength steel shanks.
- | Three Point Hitch, Category III, 4-N.
- | 7/8" diameter, Grade 2 shear bolt.
- | 20° forward swept shanks.
- | Heavy-duty stands.
- | Two, single, six-bolt hub gauge wheels

Optional Equipment

- | Spring loaded swivel coulters, 20" disk, 1" x 3" - high strength steel shank.



ROME PLOW EQUIPMENT CO., LLC

475 Sixth Street
P.O. Box 48,
Cedartown, GA 30125, USA
www.romeplow.com

Telephone: (770) 748-4450
(800) 241-7860 (USA)
Fax: (800) 553-2865 (USA)
Fax: 770-748-4427

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.