



Series:

RAFS-EP Bottomless Finishing Scraper

For use with tractors in the 300 – 600hp range.



FEATURES:

- Capable of utilizing a single or dual mast machine control system.
- Excellent for all leveling applications.
- Smooth and maintain access roads or haul roads.
- Rework washed out terraces.
- Up to 3" (102mm) cutting depth.
- Hydraulically controlled end pull drawbar.
- End pull transport system reduces transport width to 13'-8" (4.2m)
- Reversible and replaceable side cutter blades.
- Offset walking beam transport unit provides stability at higher operating speeds.
- Rear operating axle can be split to walk contours.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series RAFS-EP Bottomless Finishing Scraper

Model Number	Capacity yd ³ (m ³)	Overall Transport Dimensions			Suggested Engine Hp		Net Weight lbs (kg)
		Transport Length ft/in (m)	Cutting Width ft/in (m)	Height ft/in (m)	4 Mph	6 Mph	
RAFS-24EP	14.3 (11)	30'-4" (9.2)	24'-0" (7.3)	7'-8" (2.4)	300	450	19,565 (8875)
RAFS-30EP	17.9 (14)	36'-4" (11.1)	30'-0" (9.1)	7'-8" (2.4)	350	600	22,950 (10,410)

* Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. One rear tractor hydraulic circuits required for scraper operation.

Standard Equipment:

- Hydraulically controlled end pull drawbar.
- Laser or GPS receiver platforms.
- Breakaway front tongue.
- Four 21.5 x 16.1 tires on the operating transport, and two 16.5 x 16.1 tires on the end pull transport.
- Adjustable front hitch clevis height.
- Reversible and replaceable cutting edges and side cutter blades.
- Drawbar jack and safety chain.

Optional Equipment:

- Laser valve group (without laser).
- Light group.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com