



Series:

RALSE-HD

Gateless Ejector Scraper

For use with tractors in the 200 – 400hp range.



FEATURES:

- Designed for agricultural and construction earthmoving, land forming, and precision laser/GPS leveling.
- Hydraulics adapt for single or dual slope laser/GPS control.
- Optisurface compatible.
- Excellent tool for farm leveling, reworking or building terraces, and road maintenance
- Adjustable front hitch to fit drawbars between 18 and 24 inches high.
- Dual purpose hydraulics controls the transport unit and the depth of cut.
- Walking beam axle provides stability to scraper when operating at higher speeds.
- Removable tongue for narrower transport on a trailer
- Standard 21.5 tires give the industry's highest flotation on a gateless ejector.
- Can be containerized for overseas shipping.



Scan the code to visit our
website today:

www.romeplow.com



Specifications:

Series RALSE-HD Gateless Finishing Ejector Scraper

Model Number		RALSE-14	RALSE-16
Capacity: yd ³ (m ³)		12 (9.2)	14 (10.7)
Overall Dimensions <i>handrail top</i>	Length: ft/in (m)	22'-6" (6.9)	22'-6" (6.9)
	Width: ft/in (m)	15'-4" (4.7)	17'-4" (5.3)
	Height: ft/in (m)	9'-3" (2.8)	9'-3" (2.8)
Bucket Dimensions	Length: ft/in (m)	4'-7" (1.4)	4'-7" (1.4)
	Width: ft/in (m)	14'-0" (4.3)	16'-0" (4.9)
	Height: ft/in (m)	3'-9" (1.1)	3'-9" (1.1)
Transport Clearance: in (mm)		16" (406)	16" (406)
Net Weight: lbs (kg)		16,250 (7386)	17,300 (7864)
Payload Weight @ 2250 lb/yd ³ : lbs (kg)		27,000 (12,247)	36,000 (16,330)
Number of Tires and Size		(4) - 21.5 x 16.1	(4) - 21.5 x 16.1
Width of Cut: ft/in (m)		14'-0" (4.3)	16'-0" (4.9)
Suggested Minimum Engine Horsepower		250 – 300	300 – 350
Number of Blades and Size: ft/in (m)		(2) - 7'-0" (2.1) Reversible	(2) - 8'-0" (2.4) Reversible
Type of Hitch		Horizontal Pin Scraper Hitch – Optional Vertical Pin AG Hitch	

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com