



Series:

## **RP-14CS10      Pivot Dump Carry-All Scraper**

For use with tractors in the 250 - 300 hp range.



### **FEATURES:**

- Designed for heavy agricultural and construction earthmoving, land forming and laser leveling with easy to load bucket.
- Ruggedly built with the material electrically welded for maximum strength and rigidity.
- Four individually mounted 20.5 x 25 – 20PR tires.
- Units can be used in single or tandem configurations and are laser adaptable.
- Three piece, reversible, heat treated carbon steel blade has the extended center section with optional frost bit which reduces tractor horsepower requirements and extends blade life.
- Heavy duty yoke type multi-positional hitch with tongue assembly.
- Hydraulic control system and cylinders are designed to give precision cuts and fast spreading operation.
- Quick hitch of hydraulic lines at rear of tractor to facilitate maximum utilization of tractor in other work.



Scan the code to visit our website today:

[www.romeplow.com](http://www.romeplow.com)



## Specifications:

### Series RP-14CS10 Pivot Dump Scraper

|                                    |                                          |                              |                  |
|------------------------------------|------------------------------------------|------------------------------|------------------|
| Width of Cut:                      | 10'-0" (3.1m)                            | Shipping Weight:             | 15,240 (6,913kg) |
| Struck Capacity:                   | 10.7yd <sup>3</sup> (8.1m <sup>3</sup> ) | Scraper Weight Distribution: |                  |
| Heaped Capacity:                   | 14yd <sup>3</sup> (10.5m <sup>3</sup> )  | Tongue:                      | 33%              |
| Payload Heaped Capacity:           | 31,500 (14,288kg)                        | Wheels:                      | 67%              |
| Overall Dimensions:                |                                          | Number of Tires:             | 4                |
| Length:                            | 20'-4" (6.2m)                            | Tire Size:                   | 20.5 x 25 – 20PR |
| Width:                             | 11'-7" (3.5m)                            | Floor Thickness:             | 3" (76mm)        |
| Height:                            | 5'-10" (1.8m)                            | Reversible Cutting Edges:    | Yes              |
| Bowl Dimensions:                   |                                          | Tandem Kit Available:        | Yes              |
| Length:                            | 8'-0" (2.4m)                             | Loading Type:                | Direct           |
| Width:                             | 10'-0" (3.1m)                            | Laser/GPS Adaptable:         | Yes              |
| Height:                            | 3'-9" (1.1m)                             | Hitch Type:                  | Yoke             |
| Width Outside to Outside of Tires: | 10'-0" (3.1m)                            | Special Tractor Drawbar:     | Required         |
| Transport Clearance:               | 13" (330mm)                              | Suggested Engine Horsepower: | 250 – 300        |

\*Engine horsepower are suggested ranges and vary according to soil conditions and weight added to scraper.

**NOTE:** This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: [romeplow.com](http://romeplow.com)