



Series:

RP-18E10

Ejector Scraper

For use with tractors in the 300 – 500hp range.



FEATURES:

- Designed for use in agriculture; general, road, and levee construction; site preparation; pond building; cutting and maintaining irrigation ditches; and land leveling.
- Scraper features moving ejector to push materials over a fixed blade.
- Low tongue-weight ratio reduces drawbar weight and lessens the weight on the tractors rear axle for improved service life.
- Industry largest pins with replaceable bushings, used throughout the implement, provides improved durability in the roughest conditions.
- Laser or GPS adaptable and Optisurface compatible.
- Rear tires are offset for increased stability. Available with 20.5 x 25 or 23.5 x 25 tires.
- Available with a straight fixed blade for agricultural uses or with a staggered frost bit blade for bulk moving / construction applications.
- A bolt on rear hitch is available to fit any pin size in the industry, allowing operators to pull tandem scrapers.



Scan the code to visit our website today:

www.romeplow.com



Specifications:

Series RP-18E10 Ejector Scraper

Width of Cut:	10'-6" (4.4m)	Suggested Engine Horsepower:	300 – 500
Struck Capacity:	16yd ³ (12.2m ³)	Scraper Weight Distribution:	
Heaped Capacity:	18yd ³ (16.8m ³)	Tongue:	25%
Payload Heaped Capacity:	53,360 (24,204kg)	Wheels:	75%
Overall Dimensions:		Number of Tires:	4
Length:	27'-9" (8.4m)	Tire Size: Standard	20.5 x 25
Width:	11' 11" (3.6m)	Optional	23.5 x 25
Height:	8' 5" (2.5m)	Floor Thickness:	3" (76mm)
		Reversible Cutting Edges:	Yes
Bowl Dimensions:		Frost Bit:	Optional
Length:	9'-0" (2.7m)	Tandem Ready:	Optional
Width:	10' 6" (3.2m)	Loading Type:	Direct
Height:	5'-4" (1.3m)	Laser/GPS Adaptable:	Yes
Width Outside to Outside of Tires:	10' 6" (3.2m)	Laser Receiver Platform:	Optional
Transport Clearance:	20" (508mm)	Hitch Type:	Yoke
Shipping Weight:	28,678 (13,035kg)	Special Tractor Drawbar:	Required

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com