



Series:

RP-18E14.5

Ejector Scraper

For use with tractors in the 375 – 600hp range.



FEATURES:

- Designed for use in agriculture; general, road, and levee construction; site preparation; pond building; cutting and maintaining irrigation ditches; and land leveling.
- Scraper features moving ejector to push materials over a fixed blade.
- Low tongue-weight ratio reduces drawbar weight and lessens the weight on the tractors rear axle for improved service life.
- Industry largest 3" (76mm) pins with replaceable bushings used throughout the implement provides improved durability in the roughest conditions.
- Laser or GPS adaptable.
- Optisurface compatible.
- Available with a straight fixed blade for agricultural uses or with a staggered frost bit blade for construction type applications.
- Heavy duty router bits with two mounting positions. Once the bits wear just lower to the second mounting position to give the bits double the life expectancy.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series RP-18E14.5 Ejector Scraper

Width of Cut:	14'-6" (4.4m)	Suggested Engine Horsepower:	375 – 600
Struck Capacity:	15yd ³ (11.5m ³)	Scraper Weight Distribution:	
Heaped Capacity:	18yd ³ (13.8m ³)	Tongue:	25%
Payload Heaped Capacity:	52,210 (23,682kg)	Wheels:	75%
Overall Dimensions:		Number of Tires:	6
Length:	27'-9" (8.4m)	Tire Size:	20.5 x 25
Width:	16'-1" (4.9m)	Floor Thickness:	3" (76mm)
Height:	6'-7" (2.0m)	Reversible Cutting Edges:	Yes
Bowl Dimensions:		Frost Bit:	Optional
Length:	8'-0" (2.4m)	Tandem Ready:	Optional
Width:	14'-6" (4.4m)	Loading Type:	Direct
Height:	4'-4" (1.3m)	Laser/GPS Adaptable:	Yes
Width Outside to Outside of Tires:	14'-6" (4.4m)	Laser Receiver Platform:	Optional
Transport Clearance:	20" (508mm)	Hitch Type:	Yoke
Shipping Weight:	27,790 (12,605kg)	Special Tractor Drawbar:	Required

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com