



Series:

RP-CFB

Pivot Dump Fixed Blade Scraper

For use with tractors in the 200 – 360hp range.



FEATURES:

- Designed for precision land forming and maintenance of field irrigation and drainage efficiency.
- Fixed blade feature is designed specifically for achieving a smooth, precision laser finish.
- Direct loading lets the loading pressure push the soil into the bucket.
- Units can be used in single or tandem configurations.
- Laser and GPS adaptable.
- Large throat opening allows for problem free material ejection.
- Low tongue-weight ratio reduces drawbar weight and lessens the weight on the tractors rear axle for improved service life.
- Optional equipment: Laser/GPS receiver bracket & tandem hydraulic group.



Scan the code to visit our
website today:

www.romeplow.com



Specifications:

Series RP-CFB Pivot Dump Fixed Blade Scraper

Model Number:	RP-120CFB	RP-150CFB
Width of Cut:	12'-0" (3.7m)	14'-0" (4.3)
Struck Capacity:	8.6yd ³ (6.6m ³)	10.6yd ³ (8.1m ³)
Heaped Capacity:	12yd ³ (9.2m ³)	15yd ³ (11.5m ³)
Payload Heaped Capacity:	27,000 (12,247kg)	33,750 (15,286kg)
Overall Dimensions:		
Length:	22'-2" (6.8m)	20'-5" (6.2m)
Width:	13'-5" (4.1m)	15'-7" (4.8m)
Height:	5'-10" (1.8m)	6'-6" (1.9m)
Bowl Dimensions:		
Length:	6'-0" (1.8m)	6'-0" (1.8m)
Width:	12'-0" (3.7m)	14'-0" (4.3m)
Height:	3'-6" (1.1m)	3'-5" (1.0m)
Shipping Weight:	17,700 (6623kg)	19,950 (7258kg)
Transport Clearance:	16" (406mm)	14" (356mm)
Suggested Horsepower:	200 – 250	225 – 360
Number of Tires:	4	4
Tire Size:	20.5 x 25 – 16PR	20.5 x 25 – 16PR
Floor Thickness:	2-3/8" (60mm)	2-3/8" (60mm)
Reversible Cutting Edges:	Yes	Yes
Tandem Capable:	Yes	Yes
Loading Type:	Direct	Direct
Laser/GPS Adaptable:	Yes	Yes
Hitch Type:	Yoke	Yoke
Special Tractor Drawbar:	Required	Required

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com