



Series:

RSR

Inline Subsoiler Ripper

For use with tractors in the 108 – 354hp range.



FEATURES:

- Mainframe constructed of tough, high-strength 7" (178mm) x 7" (178mm) x 3/8" (10mm) welded rectangular tubing.
- Up to 24" (610mm) maximum depth of penetration.
- Bolt-on shanks and coulters permit quick changes in spacing when desirable.
- Deep soil mulching action reduces water erosion and helps the farmer field produce the highest yield possible while complying with today's strict conservation and erosion regulations.
- Keeps moist soil beneath the surface and away from the sun and wind.
- Provides a deep, clean "slice" that breaks up hardpan to increase water intake, reduce water runoff and enhance root structure environment for superior crop growth.
- Shear bolt protection.
- Gauge wheels assure accurate penetration control in shallow or deep applications.
- Fits the Three Point Hitch - Category III, 4-N to make transportation between jobs easier.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series RSR Inline Subsoiler Ripper

Model Number	Width of Frame ft/in (m)	Number of Shanks	Shank Spacing in (mm)	Suggested Engine Horsepower	Net Weight ft/in (m)
RSR11-3	11'-0" (3.4)	3	36" (914) – 40" (1016) – 60" (1524)	108 – 138	2382 (1081)
RSR11-5	11'-0" (3.4)	5	30" (762)	180 – 210	2305 (1046)
RSR16-5	16'-0" (4.9)	5	36" (914) – 40" (1016)	180 – 210	2740 (1243)
RSR16-7	16'-0" (4.9)	7	30" (762)	252 – 282	3092 (1403)
RSR21-7	21'-0" (6.4)	7	36" (914) – 40" (1016)	252 – 282	3527 (1600)
RSR21-9	21'-0" (6.4)	9	30" (762)	324 – 354	4314 (1957)

Note: Please specify three point arrangement when ordering.

Standard Equipment:

- 1-1/4" (32mm) x 8" (203mm) high strength steel shanks.
- 20° forward swept shanks.
- 7/8" (22mm) diameter shear bolts.
- Heavy duty stands.
- Operator's manual container.

Optional Equipment:

- Spring loaded swivel coulters with 20" (508mm) diameter disks.
- (2) gauge wheels with single six-bolt hubs.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com