



Series:

RVR

“V” Shaped Subsoiler Ripper

For use with tractors in the 44 – 250hp range.



FEATURES:

- Deep soil mulching action reduces water erosion and helps farmers produce the highest yield possible while complying with today's strict conservation and erosion regulations.
- Provides a deep, clean “slice” that breaks up hardpan to increase water intake, reduce run off and enhance root structure environment for superior crop growth.
- Keeps moist soil beneath the surface and away from the sun and wind.
- Mainframe constructed of high strength 7” (178mm) x 7” (178mm) x 3/8” (10mm) welded square tubing.
- Bolt on shanks and coulters permit quick changes in spacing when desirable.
- Shanks are shear bolt protected.
- Up to 32” (813mm) maximum depth of penetration.
- Gauge wheels assure accurate penetration control in shallow or deep applications.
- Available for category II, III, and IV three point hitches.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series RVR “V” Shaped Subsoiler Ripper

Model Number	Frame Width ft/in (m)	Number of Shanks	Shank Spacing in (mm)	Suggested Engine Horsepower	Net Weight lbs (kg)
RVR14-190	14'-0" (4.3)	1	CENTERED	44 – 74	3018 (1369)
RVR14-390	14'-0" (4.3)	3	24" – 36" (610-914)	132 – 162	3600 (1633)
RVR14-590	14'-0" (4.3)	5	24" – 36" (610-914)	220 – 250	4501 (2042)

Note: Please specify three point arrangement when ordering.

Standard Equipment:

- Heavy duty 7" (178mm) x 7" (178mm) x 3/8" (10mm) square tube framework.
- 1-1/4" (32mm) x 8" (203mm) high strength steel shanks.
- 20° forward swept shanks that are shear bolt protected.
- Two gauge wheels with six bolt hubs.
- Operator's manual container.

Optional Equipment:

- 20" (508mm) diameter spring loaded coulters.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com