



Series:

TACW

Wheel Offset Disk Harrow

For use with tractors in the 95 – 209hp range.



FEATURES:

- For deep plowing, plowing in heavy trash, mixing and aerating.
- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- High gang carrier design to prevent trash build up and clogging.
- Combines thorough mixing and aerating with easy maneuverability and transportability.
- Up to 693lbs (314kg) of weight per disk blade depending on model with an average of 631lbs (286kg).
- Up to 10" (254mm) maximum depth of penetration with standard 32" (813mm) diameter disk blades.
- Equipped with Timken dual tapered roller bearings.
- Adjustable disk blade scrapers.
- Dual purpose transport unit for transportability and penetration control.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series TACW Wheel Offset Disk Harrow

17-3/4" (450mm) disk spacing; 2-1/8" (54mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TACW-10	6'-6" (2.0)	10	95 – 120	693 (314)	6,925 (3141)
TACW-12	8'-0" (2.4)	12	105 – 130	640 (290)	7,678 (3483)
TACW-16	11'-0" (3.4)	16	168 – 193	624 (283)	9,980 (4527)
TACW-20	14'-0" (4.3)	20	184 – 209	568 (258)	11,345 (5146)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 32" (813mm) diameter x 3/8" (10mm) thick, cutout (notched) deep concavity disk blades.
- Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. TACW-10 thru TACW-16: 12.5L x 15 – 12 ply. TACW-20: 16.5L x 16.1 – 10 ply.

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Two heavy duty gang wrenches.
- Drawbar jack stand and safety chain.

Optional Equipment:

- 32" (813mm) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Oil Bath bearings.
- Light group.
- Cylinder rod stops for positive depth control adjustment.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com