



Series:

TACWR Wheel Offset Disk Harrow

For use with tractors in the 214 – 359hp range.



FEATURES:

- For deep plowing, plowing in heavy trash, mixing and aerating.
- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- Combines thorough mixing and aerating with easy maneuverability and transportability.
- Fabricated spacers are manufactured with special steel for high compression and tensile strength. This gives the spacers approximately double the durability of cast spacers.
- Heavy duty moldboard style adjustable disk blade scrapers.
- Equipped with greaseable Timken dual tapered roller bearings.
- High gang carrier design to prevent trash build up and clogging.
- Up to 715lbs (324kg) of weight per disk blade depending on model with an average of 702lbs (318kg).
- Full range of adjustments to control depth of penetration – up to 13" (330mm) with 36" (914mm) diameter disk blades.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series TACWR Wheel Offset Disk Harrow

17-3/4" (450mm) disk spacing; 2-1/2" (64mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TACWR-12	8'-0" (2.4)	12	214 – 243	715 (324)	8,575 (3890)
TACWR-16	11'-0" (3.4)	16	284 – 314	709 (322)	11,339 (5143)
TACWR-20	14'-0" (4.3)	20	331 – 359	681 (309)	13,621 (6178)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 36" (914mm) diameter, 1/2" (13mm) thick, cutout deep concavity disk blades.
- Fabricated spacers made from A53 steel.
- Heavy duty moldboard style adjustable disk blade scrapers.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. All Models - 16.5 x 16.1.
- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Drawbar jack stand and safety chain.

Optional Equipment:

- Cylinder rod stops for positive depth control adjustment.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com