



Series:

TB

Tough Boy Drag (Bottomless) Scraper

For use with tractors in the 20 – 50hp range.



FEATURES:

- Designed for moving soil, prepping yards for seeding, and leveling fields and driveways.
- Available in 5' (1.5m) and 6' (1.8m) widths.
- Computer aided design increases efficiency and performance.
- Rigid construction insures leveling accuracy.
- Positive cutting action.
- TB-5 comes standard with four scarifier shanks. TB-6 comes standard with six scarifier shanks.
- Adjustable clevis hitch keeps the scraper level with your tractor, preventing material loss and additional wear.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series TB Tough Boy Drag (Bottomless) Scraper

Model Number	Working Width ft/in (m)	Overall Dimensions			Suggested Engine Horsepower	Net Weight lbs (kg)
		Length ft/in (m)	Width ft/in (m)	Height ft/in (m)		
TB-5	5'-0" (1.5)	8'-2" (2.5)	5'-1" (1.6)	2'-6" (0.8)	20 – 50	650 (295)
TB-6	6'-0" (1.8)	8'-2" (2.5)	6'-1" (1.9)	2'-6" (0.8)	20 – 50	750 (340)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. One rear tractor hydraulic circuit required for scraper operation.

Standard Equipment:

- 3/8" (10mm) side plate and moldboard.
- Two tires rated 900lbs (400kg) each.
- Adjustable front hitch.
- 6" (152mm) road grader blades.
- Four scarifier shanks (model TB-5).
- Six scarifier shanks (model TB-6).
- Drawbar jack stand and safety chain.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com