



Series:

TBW

Wheel Offset Disk Harrow

For use with tractors in the 58 – 216hp range.



FEATURES:

- Heavy duty proven design with rugged boxed angle construction welded for maximum strength and rigidity.
- High gang carrier design to prevent trash build up and clogging.
- Levels, cuts, and mixes to full working depth.
- Up to 277lbs (126kg) of weight per disk blade depending on model with an average of 253lbs (115kg).
- Up to 9" (229mm) maximum depth of penetration with standard 26" (660mm) diameter disk blades.
- Equipped with Timken dual tapered roller bearings.
- Optional reliable, heavy duty, dual tapered 11" (279mm) oil-bath roller bearings with cast housings for increased life and minimized down time.
- Adjustable disk blade scrapers.
- Dual purpose transport unit for transportability and penetration control.



Scan the code to visit our
website today:
www.romeplow.com



Specifications:

Series TBW Wheel Offset Disk Harrow

11" (279mm) disk spacing; 1-5/8" (41mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TBW-16	7'-0" (2.1)	16	58 – 88	275 (125)	4400 (1996)
TBW-20	8'-6" (2.6)	20	67 – 97	243 (110)	4850 (2200)
TBW-24	10'-6" (3.2)	24	81 – 111	240 (109)	5750 (2608)
TBW-28	12'-0" (3.7)	28	98 – 128	250 (113)	7000 (3175)
TBW-32	14'-6" (4.4)	32	120 – 148	234 (106)	7500 (3402)
TBW-40	18'-0" (5.5)	40	186 – 216	277 (126)	11,080 (5026)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- Adjustable disk blade scrapers.
- 26" (660mm) diameter x 5/16" (8mm) thick; cutout (notched) deep concavity disk blades.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. TBW-16 – TBW-24: 9.5L x 15 10ply. TBW-28 & TBW-32: 12.5L x 15 – 12 ply. TBW-40: 16.5L x 16.1 – 10 ply.

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Drawbar jack stand and safety chain.

Optional Equipment:

- 28" (711mm) diameter x 5/16" (8mm) thick, cutout (notched) deep concavity disk blades.
- Timken dual tapered oil-bath bearings.
- Drawbar with track type clevis.
- Cylinder rod stops.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com