



Series:

TRCW-18, 20 & 24

Wheel Offset Disk Harrow

For use with tractors in the 425 – 650 hp range.



FEATURES:

- For deep plowing, plowing in heavy trash, mixing and aerating.
- Heavy duty proven design with rugged construction welded for maximum strength and rigidity.
- Adjustable disk blade scrapers.
- Equipped with Timken dual tapered roller bearings.
- High gang carrier design to prevent trash build up and clogging.
- Heavy duty torsion tube for distributing the torque generated by the front right gang.
- Hydraulic tongue leveler with nitrogen accumulator.
- Up to 1308lbs (593kg) of weight per disk blade depending on model.
- Standard 13" (330mm) depth of penetration with 36" (914mm) diameter disk blades.
- Optional 16" (381mm) depth of penetration with 42" (1.07m) diameter disk blades.



Scan the code to visit our website today:

www.romeplow.com



Specifications:

Series TRCW Wheel Offset Disk Harrow

20" (508mm) disk spacing; 2-1/2" (64mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TRCW-18	14'-3" (4.3)	18	425 – 575	1308 (593)	23,550 (10,682)
TRCW-20	16'-0" (4.9)	20	450 – 600	1220 (553)	24,400 (11,068)
TRCW-24	19'-6" (5.9)	24	500 – 650	1117 (507)	26,810 (12,161)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. Two rear tractor hydraulic circuits required for harrow operation.

Standard Equipment:

- 36" (914mm) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Hydraulic tongue leveler with nitrogen accumulator.
- Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty fabricated steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 4 each 385/R65 22.5.
- Category 4 hitch

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Drawbar jack stand and safety chain.

Optional Equipment:

- 42" (1.07m) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Cylinder rod stops.
- Light group.
- Oil Bath Bearings



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com