



Series:

VR-7500 “V” Shaped Subsoiler Ripper

For use with tractors in the 155 – 309hp range.



FEATURES:

- Breaks up hardpan, aids in root penetration, and decreases water runoff.
- Main Frame is constructed of tough, high strength 7" (178mm) x 7" (178mm) x 1/2" (13mm) steel for maximum durability.
- Maximum penetration depth up to 19" (483mm).
- Available with 24" (610mm) or 30" (762mm) shank spacing.
- Gauge wheels equipped with turnbuckles for accurate depth control.
- Wheel hubs equipped with tapered roller bearings.
- Three point hitch allows for easy transportation between jobs.
- Compatible with any three point hitch configuration.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series VR-7500 "V" Shaped Subsoiler Ripper

Model Number	Number of Shanks	Maximum Penetration ft/in (m)	Transport Width ft/in (m)	Suggested Engine Horsepower	Net Weight lbs (kg)
VR-7500-524	5	19" (493)	13'-7" (4.1)	155 – 185	4100 (1860)
VR-7500-530	5	19" (493)	14'-9" (4.5)	155 – 185	4200 (1905)
VR-7500-724	7	19" (493)	13'-7" (4.1)	217 – 247	4880 (2214)
VR-7500-730	7	19" (493)	17'-7" (5.4)	217 – 247	5022 (2278)
VR-7500-924	9	19" (493)	17'-7" (5.4)	279 – 309	5627 (2552)

Note: Please specify three point arrangement when ordering.

Standard Equipment:

- Heavy duty 7" (178mm) x 7" (178mm) x 1/2" (13mm) square tube framework.
- 1-1/2" (38mm) high strength T-1 swivel shanks equipped with wedge type points.
- 5/8" (16mm) shear bolts.
- Four 11L x 15 gauge wheel assemblies.
- Heavy duty stand.

Optional Equipment:

- Hard faced wing sweeps.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com