



Series:

TRW-S & TRW

Woods Special Wheel Offset Disk Harrow

For use with tractors in the 253 – 338hp range.



FEATURES:

- TRW-S has special reinforcement for woods site preparation and other severe applications.
- Includes strengthened gang carriers, drawbar, offset bar, stabilizer, latch, bearing standards and bearing brackets.
- High gang carrier design to prevent trash build up and clogging.
- Adjustable disk blade scrapers.
- Equipped with Timken dual tapered roller bearings.
- Up to 810lbs (367kg) of weight per disk blade depending on model with an average of 722lbs (328kg).
- Up to 11" (279mm) maximum depth of penetration with standard 32" (813mm) diameter disk blades.



Scan the code to visit our website today:

www.romeplow.com



Specifications:

Series TRW-S & TRW Woods Special Wheel Offset Disk Harrow

14" (356mm) disk spacing; 2-1/2" (64mm) round axles; Equipped with Timken dual tapered roller bearings.

Model Number	Width of Cut ft/in (m)	Number of Disks	Suggested Engine Horsepower	Weight Per Disk lbs (kg)	Net Weight lbs (kg)
TRW-16S	9'-0" (2.7)	16	253 – 283	810 (367)	12,963 (5880)
TRW-20S	11'-0" (3.4)	20	273 – 303	703 (319)	14,068 (6381)
TRW-24	13'-6" (4.1)	24	308 – 338	653 (296)	15,672 (7109)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to harrow. Per ASAE S290.1 – Width of cut will vary with gang angle and disk blade diameter.

NOTE: This harrow requires hydraulic control. One rear tractor hydraulic circuit required for harrow operation.

Standard Equipment:

- 32" (813mm) diameter x 1/2" (13mm) thick, cutout (notched) deep concavity disk blades.
- Adjustable disk blade scrapers.
- Heat treated alloy steel gang axles.
- Heavy duty cast steel spacer spools.
- Heavy duty bearing wear plates.
- New industrial tires – 2 each. All models: 15 x 22.5 – 16 ply.

- Hydraulic control group includes cylinders, hose holders, and hoses with fittings to reach rear of tractor.
- Drawbar jack stand and safety chain.

Optional Equipment:

- Cylinder rod stops.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: romeplow.com