



Series:

GS Motor Grader Sloper

Compatible with any make and model motor grader.



FEATURES:

- Economically dress road shoulders; construct and maintain ditches; shape banks on cuts and fills; and numerous other sloping and leveling operations.
- Heavy-duty 16' (4.9m) long x 3/4" (19mm) thick x 20" (508mm) wide moldboard blade made from high strength steel with replaceable cutting edges and end bits.
- Full hydraulic control from motor grader seat allows operation completely independent of the standard motor grader blade.
- Available with a fixed or sliding mount with 32" (813mm) side shift.
- Single stage pull bar allows for an 80° sloping range. Two stage pull bar allows for a 130° sloping range.
- Sloping angle hydraulically controlled from 60° up to 60° down.
- Hydraulically controlled heel lift with 24" (610mm) vertical range.
- 25° blade pitch adjustment.



Scan the bar code to visit
our website today:
www.romeplow.com



Specifications:

Series GS Motor Grader Sloper

Model Number	Blade Dimensions			Sloping Range		Horizontal Sloping Range	Approx. Weight* lbs (kg)
	Length ft/in (m)	Thickness in (mm)	Width in (mm)	Single Pullbar	Double Pullbar		
GS-16	16'-0" (4.9)	3/4" (19)	20" (508)	80°	130°	60°	6520 (2957)
COMPATIBLE WITH ANY MAKE AND MODEL MOTOR GRADER							

*Net weight will vary on make and model of motor grader; and the pull bar and mount types.

NOTE: This implement requires hydraulic control. Two tractor hydraulic circuits required for single stage pull bar. Four tractor hydraulic circuits required for two stage pull bar.

Standard Equipment:

- Available in fixed or sliding mount.
- Available with single stage pull bar for pulling material toward grader.
- Available with two stage pull bar for casting material away from grader.
- High strength square tube pull bar.
- Hardened bushings, pins and swivel joints.
- High carbon steel moldboard blade.
- Replaceable end bits and overlays.
- Hydraulic group.

Optional Equipment:

- 4' (1.2m) blade extension.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com