



Series:

**RLS**

## **Drag (Bottomless) Scraper**

For use with tractors in the 60 – 300hp range.



### **FEATURES:**

- Computer aided design increases efficiency and performance.
- Excellent for small or medium farm leveling.
- Smooth and maintain access roads or haul roads.
- Reworks washed out terraces.
- Up to 3" (102mm) cutting depth.
- Rigid construction insures leveling accuracy.
- Reversible and replaceable main cutting edges.
- Replaceable side router bits.
- Offset walking beam transport unit provides stability at higher operating speeds.
- Hydraulics adapt for laser control.
- Built in laser/GPS mounting platforms for single or dual mast control (extra laser mast must be purchased for a dual control system.)



Scan the bar code to visit our website today:

[www.romeplow.com](http://www.romeplow.com)



## Specifications:

### Series RLS Drag (Bottomless) Scraper

Model Number	Capacity yd <sup>3</sup> (m <sup>3</sup> )	Overall Dimensions			Suggested Engine Hp		Net Weight lbs (kg)
		Length ft/in (m)	Width ft/in (m)	Height ft/in (m)	4 Mph	6 Mph	
RLS-10	5.6 (1.9)	18'-0" (5.5)	10'-2" (3.1)	3'-8" (1.12)	60	80	4190 (1901)
RLS-12	6.7 (3.0)	18'-0" (5.5)	12'-2" (3.7)	3'-8" (1.12)	80	100	4470 (2028)
RLS-14	7.8 (4.2)	18'-0" (5.5)	14'-2" (4.3)	3'-8" (1.12)	110	160	4890 (2218)
RLS-16	8.9 (5.4)	18'-0" (5.5)	16'-4" (5.0)	3'-8" (1.12)	150	225	5190 (2354)
RLS-18	10 (6.5)	18'-0" (5.5)	18'-4" (5.6)	3'-8" (1.12)	175	300	5520 (2504)

\*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

**NOTE:** This scraper requires hydraulic control. One rear tractor hydraulic circuits required for scraper operation.

#### Standard Equipment:

- Replaceable side cutter bits.
- Single laser receiver platform.
- Detachable front tongue.
- All models have four each: 13.5L x 16.1L – 10 ply tires for transporting and turning.
- Adjustable front hitch clevis height.
- Pivoted double duty hitch clevis for jaw or bar mounting.
- Drawbar jack stand and safety chain.

#### Optional Equipment:

- Laser valve group (without laser).
- Light group.
- Second laser receiver platform for dual mast.



Rome Plow

475 Sixth Street

P.O. Box 48

Cedartown, GA 30125, USA

Telephone: 770.748.4450

Fax: 770.748.4427

Website: [romeplow.com](http://romeplow.com)