



Series:

RP-212HDE

Heavy Duty Ejector Scraper

For use with tractors in the 375 - 600 hp range.



FEATURES:

- Rugged 23 yd³ (17.6m³) scraper with heavy duty plate frame construction for maximum strength and rigidity.
- Rear cross member made from 10" (254mm) x 10" (254mm) x 3/4" (20mm) thick fabricated box section steel.
- Spreader bar made from 14" (357mm) x 14" (357mm) x 3/4" (20mm) thick fabricated box section steel.
- 3-1/2" (89mm) thick floor protects against pan deflection from heavy material loads and floor wear from abrasion.
- Tandem hitch capability.
- "Slip-in" bolted spindle and hub assembly.
- Highest quality hydraulic cylinders have ball joints on both base and rod ends for long life.
- Push block protects scraper rear when push loading is necessary in tough loading conditions.
- Main cutting edge is a multi-piece design making it easy to change a single section of the blade.
- Ejector is supported with six rollers that are built with wheel hub style components for easy maintenance and maximum life.



Scan the code to visit our website today:
www.romeplow.com



Specifications:
Series RP-212HDE Heavy Duty Ejector Scraper

| | | | | |
|--------------------------|---|------------------------------|----------------------------|---------------|
| Width of Cut: | 12'-6" (3.8m) | Shipping Weight: | 29,157 (13,225kg) | |
| Struck Capacity: | 18yd ³ (13.8m ³) | Scraper Weight Distribution: | Tongue: 21% Wheels: 79% | |
| Heaped Capacity: | 23yd ³ (17.6m ³) | | | |
| Payload Heaped Capacity: | 58,590 (26,576kg) | Number of Tires: | 2 | |
| Overall Dimensions: | Length: | 29'-9" (9.1m) | Tire Size: | 29.5 x 25 |
| | Width: | 13'-11" (4.2m) | Floor Thickness: | 3-1/2" (89mm) |
| | Height: | 7'-6" (2.3m) | Reversible Cutting Edges: | Yes |
| Bowl Dimensions: | Height: | 4'-2" (1.3m) | Tandem Kit Available: | Yes |
| | Depth of Spread: | 20" (0.5m) | Loading Type: | Direct |
| | Depth of Cut: | 5" (127mm) | Laser/GPS Adaptable: | Yes |
| | Width Outside to Outside of Tires: | 12'-6" (3.8m) | Hitch Type: | Yoke |
| Transport Clearance: | 18" (457mm) | Special Tractor Drawbar: | Required | |
| | | Suggested Engine Horsepower: | 375 – 600 | |

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow
 475 Sixth Street
 P.O. Box 48
 Cedartown, GA 30125, USA

Telephone: 770.748.4450
 Fax: 770.748.4427
 Website: romeplow.com