

# ROME

Series:

## RP

## Pivot Dump Carry-All Scraper

For use with tractors in the 225 - 300hp range.



### FEATURES:

- The ROME towed pivot dump, roll-out scrapers are the perfect solution to a wide range of material moving challenges and are ideally suited for moving bulk material at low cost and fast turnaround.
- Three bowl sizes with two tire arrangements are available to allow these machines to work in both high compaction and extremely soft soil environments.
- Designed for use in agriculture; general, road, and levee construction; site preparation; pond building; cutting and maintaining irrigation ditches; and land leveling.
- Ruggedly built with heavy duty plate frame construction electrically welded for maximum strength and rigidity.
- Designed to allow maximum dump clearance in order to assure maximum control of discharged material.
- One piece bowl reduces load compaction and greatly increases efficiency.
- Bolt on frost bit/stinger standard.
- All wheel hubs are fully independent.
- Tandem hitch capability with hydraulic supply kit and auxiliary kit standard.
- Bulkhead fittings protect hydraulic hookups.



Scan the bar code to visit our website today:  
[www.romeplow.com](http://www.romeplow.com)



## Specifications: Series RP Pivot Dump Carry-All Scraper

Model Number	Capacity		Width of Cut ft/in (m)	Overall Length ft/in (m)	Overall Width ft/in (m)	Number of Tires & Ply	Suggested Engine Hp		Net Weight lbs (kg)
	Heaped yd <sup>3</sup> (m <sup>3</sup> )	Struck yd <sup>3</sup> (m <sup>3</sup> )					Single	Tandem	
RP-150CS Contractors Special	15 (11.5)	11 (8.4)	10'-0" (3.1)	25'-0" (7.6)	11'-11" (3.6)	(4) 20.5x20 20 PR	225	300	19,150 (8686)
RP-150LGP Low Ground Pressure	15 (11.5)	11 (8.4)	10'-0" (3.1)	25'-8" (7.8)	11'-11" (3.6)	(2) 66x43 25 NHS	225	n/a	18,675 (8471)
RP-175CS Contractors Special	17.5 (13.4)	13.5 (10.3)	10'-0" (3.1)	25'-0" (7.6)	11'-11" (3.6)	(4) 20.5x25 20 PR	300	450	19,575 (8879)
RP-175LGP Low Ground Pressure	17.5 (13.4)	13.5 (10.3)	10'-0" (3.1)	25'-8" (7.8)	11'-11" (3.6)	(2) 66x43 25 NHS	300	n/a	19,105 (8666)
RP-180CS Contractors Special	18 (13.8)	14 (10.7)	12'-0" (3.7)	25'-0" (7.6)	13'-11" (4.2)	(4) 20.5x25 20 PR	300	450	20,635 (9360)

\*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

**NOTE:** This scraper requires hydraulic control. Two rear tractor hydraulic circuits required for scraper operation.



Rome Plow  
 475 Sixth Street  
 P.O. Box 48  
 Cedartown, GA 30125, USA

Telephone: 770.748.4450  
 Fax: 770.748.4427  
 Website: romeplow.com