



Series:

TM

Tough Man Drag (Bottomless) Scraper
For use with tractors in the 35 – 135hp range.



FEATURES:

- Designed for maintaining roads, leveling out fields, and adding in drainage ditches.
- Available in 6' (1.8m), 7' (2.1m), 8' (2.4m), 10' (3.1m), and 12' (3.7m) widths.
- Laser or GPS adaptable.
- Offset walking beam transport unit provides stability at higher operating speeds.
- Reversible and replaceable side cutter blades.
- Adjustable clevis hitch keeps the scraper level with your tractor, preventing material loss and side plate wear.
- Optional tilt adjustment angles the machine 6" (152mm) to the left or right for a more aggressive cut when crowing roads or cutting ditches.
- Wide range of optional attachments for compacting loose soil, smoothing roads, and breaking clods.



Specifications: Series TM Tough Man Drag (Bottomless) Scraper

Model Number	Working Width ft/in (m)	Overall Dimensions			Suggested Engine Horsepower	Net Weight lbs (kg)
		Length ft/in (m)	Width ft/in (m)	Height ft/in (m)		
TM-6	6'-0" (1.8)	13'-9" (4.2)	6'-0" (1.8)	4'-1" (1.3)	35 – 100	1600 (726)
TM-7	7'-0" (2.1)	13'-9" (4.2)	7'-0" (2.1)	4'-1" (1.3)	35 – 125	1866 (846)
TM-8	8'-0" (2.4)	13'-9" (4.2)	8'-0" (2.4)	4'-1" (1.3)	35 – 125	2133 (968)
TM-10	10'-0" (3.1)	13'-9" (4.2)	10'-2" (3.1)	4'-1" (1.3)	60 – 135	2650 (1202)

*Engine horsepowers are suggested ranges and vary according to soil conditions and weight added to scraper.

NOTE: This scraper requires hydraulic control. One rear tractor hydraulic circuit required for scraper operation. Additional hydraulic circuits required for tilt option and each attachment.

Standard Equipment:

- Four tires rated 900lbs (400kg) each.
- Bogie wheel assembly.
- Adjustable front clevis hitch.
- Rear hitch assembly.
- Laser rack plate.
- Detachable front tongue.
- Adjustable side cutter plates.
- 6" (152mm) road grader blades.
- Jack assembly.

Optional Equipment:

- Hydraulic scarifier bar.
- 12" (305mm) double basket roller pulverizer.
- Three bar spring tine harrow.
- 12" (305mm) smooth drum roller.
- Laser ready package.
- Hydraulic angle group.
- Rear hitch assembly.



Rome Plow
475 Sixth Street
P.O. Box 48
Cedartown, GA 30125, USA

Telephone: 770.748.4450
Fax: 770.748.4427
Website: romeplow.com